



BinTrac Bin Weighing System

From a single bin to a multi-site system with remote monitoring, BinTrac can be configured to meet your needs now and in the future.



BINTRAC® Bin Weighing System

- Easy installation on existing and loaded bins using patented load cell bracket assembly
- Real-time bin inventory by weight
- 24-hour feed use for each of the past 4 days
- Feed delivery validation
- One-year warranty covers lightning damage to load cells – 2-year extended warranty available
- Requires no calibration

Load Cell Assembly & Mounting Bracket for “W” style legs

- Easily installs on existing & loaded bins
- The bracket is the lifting mechanism
- Requires less than 1/2” bin lift
- Simplifies equal loading
- No shimming or blocking
- Field calibration is not required
- Temperature compensated load cell



#MLB-200000 10K Load
#MLB-300000 15K Load

Replacement Load Cell



#ASY-000129 10k Load Cell
#ASY-000159 15k Load Cell

Digital Summing Box

Converts analog signal to digital for measuring and averaging load cell output.



#MSA-004000 4 load cell
#MSA-006000 6 load cell
#MSA-008000 8 load cell

BinTrac Indicator

Indicator connects up to 4 bins and can be located up to 250 feet from bins.



#MCA-000001 with standard pro software

BinTrac Breeder Control

With user programmable batching weight and scheduled batching.



#MCA-000201 with standard software

Transformer

#ASY-000067 110V to 12V, Standard



Interface Cable

#CAB-000009 Interface Cable, 22AWG 4 Conductor Shielded (per foot)
#DS22204 Sensor wire 22/4 Shielded / ft.
#DS21804-1000 Sensor wire 18/4/ 1000 ft roll (for runs over 250')

