MEET THE NEW GENERATION

**EFFORTLESSLY AND** 

**IN TOTAL SAFETY!** 



DESIGNED BY PORK PRODUCERS FOR PORK PRODUCERS

Agro-Technological Products



## **IMPROVED CONTROL SYSTEM**



**Emergency STOP button** 

Twist grip throttle

Battery level indicator

ON/OFF switch

Forward/backward button

Winch control button

## STRENGTHS IN DETAIL

DESCRIPTION	CHASSIS				
	Non Art	Non Articulated		Articulated	
	MODEL 100	MODEL 200	MODEL 100A	HI/LO	
Forward speed (ft/min - m/min)	125 (38.1)	235 (71.6)	125 (38.1)	103 (32.0)	
Backward speed (ft/min - m/min)	125 (38.1)	135 (41.2)	125 (38.1)	103 (32.0)	
Drive motor	1 x 24 V	1 x 24 V 2 x 24 V 1 x 24 V		24 V	
Footboard		Included Not available		Not available	
Speed control	Variable s	Variable speed with twist grip throttle HI/LO Speed			
Motor brake		Built-in			
Battery		2 rechargeable gel batteries (12 V)			
Battery charger		Built-in (24 V)			
Winch (24 V)		4 500 lbs (2 000 kg)			
Winch cable	Galva	Galvanized steel 1/4" (stainless steel in option)			
Mast	Lock/un	Lock/unlock 180° pivotal mast including safety arms			
Flat proof tires		Gel-filled tires			
Tiltable telescopic boom		With safety arms			
Width		21" (53.3 cm)			
Length (without footboard)		42" (106.7 cm)			
Vertical mast minimal height		71" (180.3 cm)			
Vertical mast maximal height		98" (249 cm)			



1401, rue Bellevue, Saint-Lambert (Québec) Canada GOS 2W0

418-889-0566 • 1-877-776-6246 • ro-main.com